

# Parker Low Pressure (LPG) Hose Spec Sheet

Part #	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Hose Inner Tube	Hose Reinforcement	Parkrimp 26 Series
	Inch	mm	Inch	mm	psi	Mpa	Inch	mm	lbs/ft	kg/m			
SS23CG-6	5/16	8,0	0.68	17,2	425	3,0	4	100	0.16	0,24	Synthetic Rubber	One Braid Steel Wire	*
SS23CG-8	13/32	10,0	0.77	19,5	425	3,0	4 & 1/2	115	0.17	0,25	Synthetic Rubber	One Braid Steel Wire	*
SS23CG-10	1/2	12,5	0.92	23,4	425	3,0	5 & 1/2	140	0.28	0,42	Synthetic Rubber	One Braid Steel Wire	*
SS23CG-12	5/8	15,9	1.05	26,8	425	3,0	6 & 1/2	165	0.3	0,45	Synthetic Rubber	One Braid Steel Wire	*

**Count on Exotic, Parker Hannifin's CSA authorized hose assembler, for your custom hose assembly needs.**

- ❖ CSA Certified
- ❖ Exceeds CAN / CGA-8.1-M86 Type III
- ❖ Meets permeation requirements of 1,6 g/m<sup>2</sup> per day
- ❖ Meets ECE R110/R67 specification
- ❖ Meets UL21, 588, 569 specifications
- ❖ Meets the industry standards ECE110 Class 1 / UL Standard 21 LPG

## Testing:

- ❖ OHMS Testing
- ❖ Static Pressure Testing
- ❖ Electrical Conductivity of all Hose Assemblies
- ❖ Certified Tested to 2X Working Pressure

## Typical Applications Include:

- ❖ Transportation
- ❖ Agriculture
- ❖ Material Handling

\*\* Operate in Temperature Ranges from -40°F to +250°F (-40°C to +121°C) \*\*



### Exotic Automation & Supply

34700 Grand River Avenue  
 Farmington Hills, MI 48335  
 P: (248) 477-2122 F: (248) 426-3778 [sales@erpc.com](mailto:sales@erpc.com)  
[www.exoticautomation.com](http://www.exoticautomation.com)